## dyson airblade 9kJ


# Dyson backplate technical specification





Front elevation

**UPC**: 885609019628 **Item Number:** 970408-01



FLOOF

Recommended installation heights from floor	
57 ½ in (1451 mm)	
55 ¾ in (1416 mm)	
47 ½ in (1207 mm)	
42 ½ in (1079 mm)	
47 % in (1179 mm)	
49 ½ in (1256 mm)	
16 in (5 mm)	

Minimum clearance above machine		
	8 ¼ in (210 mm)	
Rear cable entry point from floor		
Male	51 in (1293 mm)	
Female	49 ½ in (1258 mm)	
Wheelchair user	41 ½ in (1049 mm)	
Child 5-8	36 ¼ in (921 mm)	
Child 8-11	40 ½ in (1021 mm)	
Child 11-14	48 ¼ in (1098 mm)	

### dyson airblade 9kJ



#### Installing the Dyson backplate

Where only unsupported plasterboard is available for installation, a Dyson backplate must be used. Fixing to unsupported plasterboard (drywall) without the aid of a Dyson backplate will not result in safe and secure installation for your machine, and may also invalidate your warranty.

If the wall you are fixing the machine to has an airgap, the fixings used must be of a sufficient length to provide a secure installation. Do not use sealant when attaching the machine to the wall.

The Dyson backplate helps protect the wall from water damage and can be used to cover holes/marks left from previously installed products.

Contact the Dyson Helpline for further information.

#### Construction

Stainless steel (brushed)

Back plate mounting bracket: Stainless steel – Brushed (304L)

#### Logistics

Net weight: 6.7 kg /14.7 lbs

Packaged weight: 11.10 kg / 24.47 lbs

Packaged dimensions:

Height: 2 ¾ in (71 mm) x Width: 26 ¼ in (664 mm) x Depth: 51 in (1295 mm)

#### Standard warranty

5 year parts and limited labor warranty

**UPC:** 885609019628 **Item Number:** 970408-01

