



# High Traction Wood Cleaner/Restorer

Instantly improves the slip resistant properties of wood flooring

## Features & Benefits

- Can be applied with a mop or auto scrubber.
- Use on any type of sealed wood floor or resilient tile, stone and concrete

## Usage Instructions

- Thoroughly sweep or dust mop the floor to remove any dirt or soil
- Dilute Swish High Traction™ 2 ounces per gallon (60mL/3.78L) with warm water
- Swish High Traction™ may be applied using either a damp mop or automatic scrubber. A two- bucket system, in which one bucket holds the Swish High Traction™ solution and one into which the soiled solution is wrung, will provide the cleanest result. Use a clean cotton or cotton/synthetic combination mop to damp mop the floor. For use in an automatic scrubber, place the Swish High Traction™ solution in the solution tank of the automatic scrubber. The solution may be applied, scrubbed, and vacuumed in one step. Following damp mopping or scrubbing, allow the floor to dry completely, but do not rinse
- To restore gloss or repair scuffs, buff or burnish the treated area with an appropriate buffing or burnishing pad with either a buffing or burnishing machine

## Caution

- May cause skin irritation
- May cause serious eye irritation
- Wear protective gloves, clothing, eye and face protection
- Dispose of contents/container in accordance with local regulation

## Product Code & Size

#9003-4      3.78 L x 4 /case