



# X4 ROVR SPECIFICATIONS

## AUTONOMOUS FLOOR SCRUBBER DRYER

Operating system	BrainOS®
Learning type	Teach & Repeat and Area Fill
Scrubbing path	500 mm dual disk
Estimated coverage per solution tank	1.860 m <sup>2</sup>
Squeegee width	551 mm
Solution tank	38 L
Recovery tank	38 L
Demisting chamber	11,4 L
Brush/pad rpm	220 rpm
Brush/pad downforce	up to 19 kg
Battery	Lithium-Ion, 90 Ah (qty: 1)
Cleaning tool attachment	Insta-Click™
Autonomous scrubbing battery time	up to 2,5 hrs
Autonomous solution delivery system	Velocity-controlled
Conventional scrubbing - pumped solution flow rates	Low: 0,30-0,68 LPM variable Med: 0,30-0,91 LPM variable High: 0,30-1,32 LPM variable
Charger type	on-board
Charger specs	50/60Hz, 100-240 VAC, 1000W Charger cord length 4,5 m
Charging time	2,2 hrs (10% > 100%)
System voltage	25,6 volts
Vacuum motor	0,45 kW
Standard sound level	as low as 66 dBA
Aisle navigation	as low as 71 cm
Aisle entrance (90 degree)	as low as 91 cm
Aisle u-turn	as low as 137 cm
Machine height	112 cm
Machine length	96 cm
Machine width	56 cm
Autonomous distance to wall	as low as 7,6 cm
Weight (tanks empty, with battery)	83 kg

For a complete selection of genuine Tennant parts, brushes and pads, please consult the X4 ROVR Parts and Consumables Reference Guide