

Version 1.1	Revision Date: 02/10/2015		SDS Number: 955-00002	Date of last issue: 01/13/2015 Date of first issue: 01/13/2015	
SECTION	1. IDENTIFICATION				
Produ	ct name	:	PURELL® Advanced Hand Rub		
Manu	facturer or supplier's	deta	ails		
			GOJO Industries, Inc.		
Addre	SS	:	One GOJO Plaza, Suite 500 Akron OH 44311		
Teleph	none	:	1 (330) 255-6000		
Emergency telephone		:	1-800-424-9300 CHEMTREC		
Recommended use of the o		chen	nical and restriction	ons on use	
Recor	nmended use	:	Hand Sanitizer		
Restrictions on use		:	This is a personal care or cosmetic product that is safe for consumers and other users under normal and reasonable foreseeable use. Cosmetics and consumer products, specifically defined by regulations around the world, are exempt from the requirement of an SDS for the consumer While this material is not considered hazardous, this SDS contains valuable information critical to the safe handling proper use of the product for industrial workplace condition as well as unusual and unintended exposures such as la spills. This SDS should be retained and available for employees and other users of this product. For specific intended-use guidance, please refer to the information provided on the package or instruction sheet.		

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification Flammable liquids	: Category 3
Eye irritation	: Category 2A
GHS Label element Hazard pictograms	
Signal Word	: Warning
Hazard Statements	: H226 Flammable liquid and vapor. H319 Causes serious eye irritation.



Version	Revision Date:	MSDS Number:	Date of last issue: 01/13/2015
1.1	02/10/2015	46955-00002	Date of first issue: 01/13/2015
Preca	utionary Statements	No smoking. P233 Keep cont P241 Use explo- equipment. P242 Use only r P243 Take prec P264 Wash skin P280 Wear prote Response: P303 + P361 + I all contaminated P305 + P351 + I for several minu to do. Continue P337 + P313 If e attention. Storage: P403 + P235 Ste Disposal:	y from heat/sparks/open flames/hot surfaces ainer tightly closed. sion-proof electrical/ ventilating/ lighting/ hon-sparking tools. autionary measures against static discharge. thoroughly after handling. ective gloves/ eye protection/ face protection. P353 IF ON SKIN (or hair): Take off immediately I clothing. Rinse skin with water/shower. P338 IF IN EYES: Rinse cautiously with water tes. Remove contact lenses, if present and easy rinsing. eye irritation persists: Get medical advice/ ore in a well-ventilated place. Keep cool. f contents/ container to an approved waste

Other hazards

Vapors may form explosive mixture with air.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous ingredients

Chemical Name	CAS-No.	Concentration (%)
Ethanol	64-17-5	>= 50 - < 70
Propan-2-ol	67-63-0	>= 1 - < 5

SECTION 4. FIRST AID MEASURES

General advice	 In the case of accident or if you feel unwell, seek medical advice immediately. When symptoms persist or in all cases of doubt seek medica advice. 	ıl
If inhaled	: If inhaled, remove to fresh air. Get medical attention if symptoms occur.	
In case of skin contact	: Wash with water and soap as a precaution. Get medical attention if symptoms occur.	
In case of eye contact	 In case of contact, immediately flush eyes with plenty of wate for at least 15 minutes. If easy to do, remove contact lens, if worn. 	ər



Version 1.1	Revision Date: 02/10/2015	MSDS Number: 46955-00002	Date of last issue: 01/13/2015 Date of first issue: 01/13/2015	
lf swa	allowed	Get medical at	ttention. DO NOT induce vomiting. ttention if symptoms occur. horoughly with water.	
Most important symptoms and effects, both acute and delayed		: Causes serious eye irritation.		
Protection of first-aiders		and use the re	: First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists.	
Notes	s to physician	: Treat sympton	natically and supportively.	

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media	Water spray Alcohol-resistant foam Dry chemical Carbon dioxide (CO2)	
Unsuitable extinguishing media	High volume water jet	
Specific hazards during fire fighting	Do not use a solid water stream as it may scatter and spr fire. Flash back possible over considerable distance. Vapors may form explosive mixtures with air. Exposure to combustion products may be a hazard to he	
Hazardous combustion prod- ucts	Carbon oxides	
Specific extinguishing methods	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Use water spray to cool unopened containers. Remove undamaged containers from fire area if it is safe so. Evacuate area.	
Special protective equipment for fire-fighters	In the event of fire, wear self-contained breathing appara Use personal protective equipment.	tus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	 Remove all sources of ignition. Use personal protective equipment. Follow safe handling advice and personal protective equipment recommendations.
Environmental precautions	: Discharge into the environment must be avoided.



Version 1.1	Revision Date: 02/10/2015	MSDS Number: 46955-00002	Date of last issue: 01/13/2015 Date of first issue: 01/13/2015		
Methods and materials for containment and cleaning up		 Prevent further leakage or spillage if safe to do so. Prevent spreading over a wide area (e.g. by containment or oil barriers). Retain and dispose of contaminated wash water. Local authorities should be advised if significant spillages cannot be contained. Non-sparking tools should be used. Soak up with inert absorbent material. Suppress (knock down) gases/vapors/mists with a water spray jet. 			
		containment to k can be pumped, container. Clean up remain absorbent. Local or national disposal of this n employed in the	brovide diking or other appropriate eep material from spreading. If diked material store recovered material in appropriate ing materials from spill with suitable regulations may apply to releases and naterial, as well as those materials and items cleanup of releases. You will need to		
		Sections 13 and	regulations are applicable. 15 of this SDS provide information regarding ational requirements.		

SECTION 7. HANDLING AND STORAGE

Technical measures	: See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.	
Local/Total ventilation	: Use with local exhaust ventilation. Use only in an area equipped with explosion proof exhaust ventilation.	
Advice on safe handling	 Do not breathe vapors or spray mist. Do not swallow. Do not get in eyes. Avoid prolonged or repeated contact with skin. Handle in accordance with good industrial hygiene and safety practice. Non-sparking tools should be used. Keep container tightly closed. Keep away from heat and sources of ignition. Take precautionary measures against static discharges. Take care to prevent spills, waste and minimize release to the environment. 	
Conditions for safe storage	 Keep in properly labeled containers. Keep tightly closed. Keep in a cool, well-ventilated place. Store in accordance with the particular national regulations. Keep away from heat and sources of ignition. 	
Materials to avoid	: Do not store with the following product types: Strong oxidizing agents	



Version	Revision Date:	MSDS Number:	Date of last issue: 01/13/2015
1.1	02/10/2015	46955-00002	Date of first issue: 01/13/2015
		•	ds ds ds bstances and mixtures d mixtures which in contact with water emit

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Ethanol	64-17-5	TWA	1,000 ppm 1,900 mg/m3	NIOSH REL
		TWA	1,000 ppm 1,900 mg/m3	OSHA Z-1
		STEL	1,000 ppm	ACGIH
Propan-2-ol	67-63-0	TWA	200 ppm	ACGIH
		STEL	400 ppm	ACGIH
		TWA	400 ppm 980 mg/m3	NIOSH REL
		ST	500 ppm 1,225 mg/m3	NIOSH REL
		TWA	400 ppm 980 mg/m3	OSHA Z-1

Ingredients with workplace control parameters

Biological occupational exposure limits

Ingredients	CAS-No.	Control parameters	Biological specimen	Sam- pling time	Permissible concentratio n	Basis
Propan-2-ol	67-63-0	Acetone	Urine	End of shift at end of work- week	40 mg/l	ACGIH BEI

Engineering measures

: Minimize workplace exposure concentrations. Use only in an area equipped with explosion proof exhaust ventilation. Use with local exhaust ventilation.

Personal protective equipment

Respiratory protection : General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and



Version 1.1	Revision Date: 02/10/2015		SDS Number: 955-00002	Date of last issue: 01/13/2015 Date of first issue: 01/13/2015
			by air purifying re- hazardous chemi- supplied respirato release, exposure	A approved respirators. Protection provided spirators against exposure to any cal is limited. Use a positive pressure air or if there is any potential for uncontrolled e levels are unknown, or any other ere air purifying respirators may not provide on.
	protection terial	:	Impervious gloves	5
Ма	terial	:	Flame retardant g	loves
Re	marks	:	on the concentrat time is not determ For special applic resistance to cher	protect hands against chemicals depending ion specific to place of work. Breakthrough hined for the product. Change gloves often! ations, we recommend clarifying the micals of the aforementioned protective ove manufacturer. Wash hands before end of workday.
Eye p	protection	:	Wear the following Safety goggles	g personal protective equipment:
Skin a	and body protection	:	resistance data a potential. Wear the followin Flame retardant a Skin contact must	e protective clothing based on chemical nd an assessment of the local exposure g personal protective equipment: antistatic protective clothing. t be avoided by using impervious protective aprons, boots, etc).
Hygie	ene measures	:	located close to the When using do not	lushing systems and safety showers are ne working place. ot eat, drink or smoke. ed clothing before re-use.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: liquid
Color	: clear, Colorless to pale yellow
Odor	: citrus
Odor Threshold	: No data available
рН	: 6.0 - 9.2
Melting point/freezing point	: No data available
Initial boiling point and boiling range	: No data available



Versi 1.1	ion	Revision Date: 02/10/2015		DS Number: 955-00002	Date of last issue: 01/13/2015 Date of first issue: 01/13/2015
	Flash p	oint	:	25 °C	
	Evapora	ation rate	:	No data available	3
	Flamma	ability (solid, gas)	:	Not applicable	
	Upper e	explosion limit	:	No data available	
	Lower e	explosion limit	:	No data available)
	Vapor p	pressure	:	No data available)
	Relative	e vapor density	:	No data available)
	Density		:	0.89 g/cm3	
	Solubili Wate	ty(ies) er solubility	:	soluble	
	Partition octanol	n coefficient: n- /water	:	Not applicable	
	Autoign	ition temperature	:	No data available)
	Decom	position temperature	:	The substance of	r mixture is not classified self-reactive.
	Viscosit Visco	y osity, kinematic	:	1,000 - 35,000 m	m2/s (20 °C)
	Explosi	ve properties	:	Not explosive	
	Oxidizir	ng properties	:	The substance of	r mixture is not classified as oxidizing.

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: Not classified as a reactivity hazard.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reac- tions	 Flammable liquid and vapor. Vapors may form explosive mixture with air. Can react with strong oxidizing agents.
Conditions to avoid	: Heat, flames and sparks.
Incompatible materials	: Oxidizing agents
Hazardous decomposition products	: No hazardous decomposition products are known.



Version 1.1	Revision Date: 02/10/2015		SDS Number: 955-00002	Date of last issue: 01/13/2015 Date of first issue: 01/13/2015
SECTIO	ON 11. TOXICOLOGICAL	INF	ORMATION	
Inf Sk Ing	ormation on likely routes nalation in contact gestion e contact	s of	exposure	
Ac	ute toxicity			
No	t classified based on avail	able	information.	
Pr	oduct:			
Ac	ute oral toxicity	:	Acute toxicity est Method: Calculat	timate: > 5,000 mg/kg tion method
	gredients: hanol:			
Ac	ute oral toxicity	:	LD50 (Rat): > 5,0	000 mg/kg
Ac	ute inhalation toxicity	:	LC50 (Rat): 124. Exposure time: 4 Test atmosphere	⊧h
Pr	opan-2-ol:			
	ute oral toxicity	:	LD50 (Rat): > 5,0	000 mg/kg
Ac	ute inhalation toxicity	:	LC50 (Rat): 72.6 Exposure time: 4 Test atmosphere	h
Ac	ute dermal toxicity	:	LD50 (Rat): > 5,0	000 mg/kg
	in corrosion/irritation t classified based on avail	able	information.	
Pr	oduct:			
Re	sult: No skin irritation			

Ingredients:

Ethanol: Species: Rabbit Method: OECD Test Guideline 404 Result: No skin irritation

Propan-2-ol:

Species: Rabbit Result: No skin irritation

Serious eye damage/eye irritation

Causes serious eye irritation.

Ingredients:



Date of last issue: 01/13/2015 Date of first issue: 01/13/2015

PURELL® Advanced Hand Rub

Version	Revision Date:	MSDS Number:
1.1	02/10/2015	46955-00002
	ies: Rabbit	eversing within 21 days

Method: OECD Test Guideline 405

Propan-2-ol:

Species: Rabbit Result: Irritation to eyes, reversing within 21 days

Respiratory or skin sensitization

Skin sensitization: Not classified based on available information. Respiratory sensitization: Not classified based on available information.

Product:

Assessment: Does not cause skin sensitization.

Ingredients:

Ethanol:

Test Type: Local lymph node assay (LLNA) Routes of exposure: Skin contact Species: Mouse Result: negative

Propan-2-ol:

Test Type: Buehler Test Routes of exposure: Skin contact Species: Guinea pig Method: OECD Test Guideline 406 Result: negative

Germ cell mutagenicity

Not classified based on available information.

Ingredients:

Ethanol: Genotoxicity in vitro	:	Test Type: In vitro mammalian cell gene mutation test Result: negative
Genotoxicity in vivo	:	Test Type: Rodent dominant lethal test (germ cell) (in vivo) Species: Mouse Application Route: Ingestion Result: negative
Propan-2-ol: Genotoxicity in vitro	:	Test Type: Bacterial reverse mutation assay (AMES) Result: negative
Genotoxicity in vivo	:	Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay) Species: Mouse Application Route: Intraperitoneal injection Result: negative



	Revision Date: 02/10/2015	MSDS Numb 46955-00002	er: Date of last issue: 01/13/2015 Date of first issue: 01/13/2015
	nogenicity assified based on availa	ble informatior	
Propa Speci Applic Expos Metho	dients: an-2-ol: es: Rat cation Route: inhalation (sure time: 104 weeks od: OECD Test Guideline It: negative		
IARC	;	equal to 0.19	t of this product present at levels greater than of 6 is identified as probable, possible or confirmed nogen by IARC.
OSH	A		t of this product present at levels greater than o 6 is identified as a carcinogen or potential carcir A.
NTP			t of this product present at levels greater than o 6 is identified as a known or anticipated carcino
-	oductive toxicity assified based on availa	ble informatior	l.
Ingre			
Ethar		Species: I Applicatio	n Route: Ingestion DECD Test Guideline 416
Ethar Effect	nol:	Species: I Applicatio Method: C Result: ne : Test Type Species: I	Mouse n Route: Ingestion DECD Test Guideline 416 gative : Two-generation reproduction toxicity study Rat n Route: Ingestion
Ethar Effect Propa Effect	nol: is on fertility an-2-ol:	Species: I Applicatio Method: C Result: ne : Test Type Species: I Applicatio Result: ne : Test Type Species: I	Mouse n Route: Ingestion DECD Test Guideline 416 gative : Two-generation reproduction toxicity study Rat n Route: Ingestion gative : Embryo-fetal development Rat n Route: Ingestion
Ethar Effect Propa Effect Effect	nol: is on fertility an-2-ol: is on fertility	 Species: I Applicatio Method: C Result: ne Test Type Species: I Applicatio Result: ne Test Type Species: I Applicatio Result: ne 	Mouse n Route: Ingestion DECD Test Guideline 416 gative : Two-generation reproduction toxicity study Rat n Route: Ingestion gative : Embryo-fetal development Rat n Route: Ingestion gative

Assessment: May cause drowsiness or dizziness.



Date of last issue: 01/13/2015 Date of first issue: 01/13/2015

PURELL® Advanced Hand Rub

Version	Revision Date:	MSDS Number:
1.1	02/10/2015	46955-00002

STOT-repeated exposure

Not classified based on available information.

Repeated dose toxicity

Ingredients:

Ethanol: Species: Rat NOAEL: 2,400 mg/kg Application Route: Ingestion Exposure time: 2 y

Propan-2-ol:

Species: Rat NOAEL: 5000 ppm Application Route: inhalation (vapor) Exposure time: 104 w Method: OECD Test Guideline 413

Aspiration toxicity

Not classified based on available information.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Ingredients: Ethanol:		
Toxicity to fish	:	LC50 (Pimephales promelas (fathead minnow)): > 1,000 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): > 1,000 mg/l Exposure time: 48 h
Toxicity to algae	:	EC50 (Chlorella vulgaris (Fresh water algae)): 275 mg/l Exposure time: 72 h Method: OECD Test Guideline 201
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	:	NOEC (Daphnia magna (Water flea)): 9.6 mg/l Exposure time: 9 d
Toxicity to bacteria	:	EC50 (Photobacterium phosphoreum): 32.1 mg/l Exposure time: 0.25 h
Propan-2-ol: Toxicity to fish	:	LC50 (Pimephales promelas (fathead minnow)): 10,000 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): > 10,000 mg/l Exposure time: 24 h
Toxicity to algae	:	ErC50 (Scenedesmus quadricauda (Green algae)): > 1,800 mg/l



rsion	Revision Date: 02/10/2015	MSDS Number: 46955-00002	Date of last issue: 01/13/2015 Date of first issue: 01/13/2015
		Exposure time	:: 8 d
Toxic	ity to bacteria	: EC50 (Pseudo Exposure time	omonas putida): > 1,050 mg/l : 16 h
Persi	stence and degrada	bility	
	dients:		
Ethar Biode	nol: gradability	: Result: Readil Biodegradation Exposure time	n: 84 %
	a n-2-ol: gradability	: Result: rapidly	degradable
Bioad	cumulative potentia	I	
Ingre	dients:		
	nol: on coefficient: n- ol/water	: log Pow: -0.35	
Propa	an-2-ol:		
Partiti	on coefficient: n- ol/water	: log Pow: 0.05	
Mobi	lity in soil		
No da	ita available		
Other	adverse effects Ita available		

Disposal methods Waste from residues	: Dispose of in accordance with local regulations.
Contaminated packaging	 Dispose of as unused product. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

International Regulation

UN number	:	UN 1987
Proper shipping name	:	ALCOHOLS, N.O.S.



Vers 1.1	sion	Revision Date: 02/10/2015		SDS Number: 955-00002	Date of last issue: 01/13/2015 Date of first issue: 01/13/2015
				(Ethanol, Propan-	-2-ol)
	Class			3	
		g group			
	Labels	g group	:	3	
			•	0	
	IATA-D				
	UN/ID No.		-	UN 1987	
	Proper shipping name		:	Alcohols, n.o.s.	
				(Ethanol, Propan-	-2-ol)
	Class		:	3	
	Packing	g group	:		
	Labels		:	Flammable Liquid	ds
	Packing	g instruction (cargo	:	366	
	aircraft				
		g instruction	:	355	
	(passe	nger aircraft)			
	IMDG-	Code			
	UN nur		:	UN 1987	
	Proper	shipping name	:	ALCOHOLS, N.C	
				(Ethanol, Propan-	-2-ol)
	Class		:	3	
	Labels	g group	:	 2	
	EmS C	ode	:	3 F-E, S-D	
		pollutant	:	no	
				-	
	-		-		OL 73/78 and the IBC Code
	Not app	plicable for product as	sup	plied.	
	Domes	stic regulation			
	49 CFF	R			
	UN/ID/	NA number	:	UN 1987	
	Proper	shipping name	:	ALCOHOLS, N.C).S.

Proper shipping name	: UN 1987 : ALCOHOLS, N.O.S.
Class	: 3
Packing group	: III
Labels	: FLAMMABLE LIQUID
ERG Code	: 127
Marine pollutant	: no

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know

CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Fire Hazard



ersion 1	Revision Date: 02/10/2015	MSDS Number: 46955-00002	Date of last issue: 01/13/2 Date of first issue: 01/13/2		
		Acute Healt	h Hazard		
SAR	A 302		lls in this material are subject to the state of SARA Title III, Section 302.		
SAR	A 313	: The following components are subject to reporting levels established by SARA Title III, Section 313:			
		Propan-2-ol	67-63-0	3.013 %	
US SI	ate Regulations				
Penn	sylvania Right To Kr	now			
	Ethanol		64-17-5	50 - 70 %	
	Water		7732-18-5	30 - 50 %	
	Propan-2-	l	67-63-0	1 - 5 %	
New .	Jersey Right To Kno	w			
	Ethanol		64-17-5	50 - 70 %	
	Water		7732-18-5	30 - 50 %	
	Propan-2-	ol	67-63-0	1 - 5 %	
California Prop 65		State of Cal	This product does not contain any chemicals known to the State of California to cause cancer, birth, or any other reproductive defects.		


AICS

: All ingredients listed or exempt.

Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), NECSI (Taiwan), TSCA (USA)





HMIS III:

HEALTH	2
FLAMMABILITY	3
PHYSICAL HAZARD	0

0 = not significant, 1 =Slight,

2 = Moderate, 3 = High

4 = Extreme, * = Chronic

Full text of other abbreviations

ACGIH ACGIH BEI		USA. ACGIH Threshold Limit Values (TLV) ACGIH - Biological Exposure Indices (BEI)
NIOSH REL		USA. NIOSH Recommended Exposure Limits
OSHA Z-1	:	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Lim- its for Air Contaminants
ACGIH / TWA	:	8-hour, time-weighted average
ACGIH / STEL	:	Short-term exposure limit
NIOSH REL / TWA	:	Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
NIOSH REL / ST	:	STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday
OSHA Z-1 / TWA	:	8-hour time weighted average
Sources of key data used to compile the Material Safety Data Sheet	:	Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agen- cy, http://echa.europa.eu/
Revision Date	:	02/10/2015

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8